

**WSZ Series  
Analog Output Module**

Model: WSZ-2DA

**製品仕様書  
Product Specifications**

This material and the information herein is the property of Fuji Electric Co.,Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party, nor used for the manufacturing purposes without the express written consent of Fuji Electric Co.,Ltd.

**富士電機株式会社  
Fuji Electric Co.,Ltd.**

REVISIONS				

	DATE	NAME	APPROVED	Fuji Electric Co.,Ltd		
DRAWN	2010-12-15	小塚	酒井	DWG NO.	WDS500025	1/2
CHECKED	--					

1.仕様  
Specifications

Spec.	Model	WSZ-2DA
Number of output point		2 points / 14-bit
Digital output value		-8192 ~ +8191 or 0 ~ 16383
Output signal range	Bipolar	Voltage : -10 ~ 10V or -5 ~ 5V, Current : -20 ~ 20mA or -10 ~ 10mA
	Unipolar	Voltage : 0 ~ 10V or 0 ~ 5V, Current : 0 ~ 20mA or 0 ~ 10mA
Maximum resolution		Voltage : 0.3mV (5V/16384), Current : 0.61μA (10mA/16384)
Accuracy		±1%
Conversion time		Conversion once for each scan
Allowable loading		Voltage : 500Ω ~ 1MΩ, Current : 0 ~ 500Ω
Isolation method		Transformer (power) and photo-coupler (signal) isolation
Power consumption		24VDC -15%/+20%, 2VA max.
Wiring mechanism		7.62mm terminal block

This material and the information herein is the property of Fuji Electric Co.,Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party, nor used for the manufacturing purposes without the express written consent of Fuji Electric Co.,Ltd.

REVISIONS			
-----------	--	--	--

	DATE	NAME	APPROVED	<b>Fuji Electric Co.,Ltd</b>	DWG NO.	<b>WDS500025</b>	2/2
DRAWN	2010-12-15	小塚	酒井				
CHECKED	--						